

# One-Way Cassette



**AUX**  
AIR CONDITIONER



# One-Way Cassette

## Specifications

	ARVC1-H028/4R1A	ARVC1-H036/4R1A	ARVC1-H036/4R1A	ARVC1-H056/4R1A	ARVC1-H071/4R1A
Model - Panel	/	/	/	/	/
Power Supply (V~,Hz,Ph)	220-240/50/1	220-240/50/1	220-240/50/1	220-240/50/1	220-240/50/1
Cooling Capacity (kw)	2.8	3.6	4.5	5.6	7.1
Heating Capacity (Kw)	3.2	4	5	6.3	8
Max. consumption (W)	40	40	45	50	50
Output Power x Fan quantity (W)	18x1	18x1	25x1	30x1	30x1
Speed (Hi/Mi/Lo) (r/min)	810	810	950	1020	1020
Indoor Air Flow (Hi/Mi/Lo) (m3/h)	600/480/360	600/480/360	720/570/450	1000/850/750	1000/850/750
Noise Level(Hi/Mi/Lo) (dB(A))	39/35/31	39/35/31	42/39/35	47/43/40	47/43/40
Net Dimension (W*H*D) (mm)	870x460x250	870x460x250	870x460x250	1180x495x290	1180x495x290
Net Weight (kg)	27	27	30	39	39
Net Dimension (W*H*D) (mm)	1070x520x33	1070x520x33	1070x520x33	1380x550x33	1380x550x33
Net weight (kg)	3	3	3	5	5
Liquid Side (mm)	6.35(1/4)	6.35(1/4)	6.35(1/4)	9.52(3/8)	9.52(3/8)
Gas Side (mm)	12.7(1/2)	12.7(1/2)	12.7(1/2)	15.88(5/8)	15.88(5/8)
Drainage (mm)	R3/4in(DN20)	R3/4in(DN20)	R3/4in(DN20)	R3/4in(DN20)	R3/4in(DN20)
Application Area (m2)	11	14	18	22	28



Type K Controller (Standard)



XK-05 Wired Controller (Optional)



Central Controller (Optional)



WiFi Controller (Optional)

## Features

■ standard ■ optional



Hydrophilic aluminum fin



Long-term Filter



0.3W Standby



Fast Cooling/Heating



Low Ambient Cooling



Intelligent Defrosting



Auto Restart Function



Self-diagnosis Function



Fresh Air Intake



Digital Tube Display



Fire-proof Electric Box



Built-in Drain Pump

Project Tender

