

Two-Way Cassette



AUX
AIR CONDITIONER



Two-Way Cassette

Specifications

	ARVC2-H028/4R1A	ARVC2-H036/4R1A	ARVC2-H045/4R1A	ARVC2-H056/4R1A	ARVC2-H071/4R1A
Model - Panel	/	/	/	/	/
Power Supply (V~,Hz,Ph)	220-240/50/1	220-240/50/1	220-240/50/1	220-240/50/1	220-240/50/1
Cooling Capacity (kw)	2.8	3.6	4.5	5.6	7.1
Heating Capacity (Kw)	3.2	4	5	6.3	8
Max. consumption (W)	62	62	85	85	94
Output Power x Fan quantity (W)	10×1	10×1	16×1	16×1	30×1
Speed (Hi/Mi/Lo) (r/min)	625	625	765	765	990
Indoor Air Flow (Hi/Mi/Lo) (m3/h)	616/523/462	616/523/462	900/765/657	900/765/657	1165/990/873
Noise Level(Hi/Mi/Lo) (dB(A))	39/36/32	39/36/32	45/41/39	45/41/39	47/43/40
Net Dimension (W*H*D) (mm)	960x520x315	960x520x315	960x520x315	960x520x315	1200x520x315
Net Weight (kg)	41	41	42	42	47.5
Net Dimension (W*H*D) (mm)	1176x630x35	1176x630x35	1176x630x35	1176x630x35	1416x630x35
Net weight (kg)	5	5	5	5	7.5
Liquid Side (mm)	6.35(1/4)	6.35(1/4)	6.35(1/4)	6.35(1/4)	9.52(3/8)
Gas Side (mm)	12.7(1/2)	12.7(1/2)	12.7(1/2)	12.7(1/2)	15.88(5/8)
Drainage (mm)	R3/4in(DN20)	R3/4in(DN20)	R3/4in(DN20)	R3/4in(DN20)	R3/4in(DN20)
Application Area (m2)	11	14	18	22	28



Type K Controller (Standard)



XK-05 Wired Controller (Optional)



Central Controller (Optional)



WiFi Controller (Optional)

Features

■ standard ■ optional



Hydrophilic aluminum fin



Long-term Filter



0.5W Standby



Fast Cooling/Heating



Low Ambient Cooling



Intelligent Defrosting



Auto Restart Function



Self-diagnosis Function



Fresh Air Intake



Digital Tube Display



Fire-proof Electric Box



Built-in Drain Pump

